



# LT50/60 Mechanical Accessories

## Motor Brackets

Dimensions (mm)	Cat. Number	Description
	6070003	<p>LT50 Motor Angle Bracket</p> <ul style="list-style-type: none"> <li>- Zinc-plated steel</li> <li>- .807 in. diameter through hole</li> <li>- Maximum motor torque - 40 Nm</li> <li>- Compatible with 9080239 idler end bearing support</li> <li>- Maximum system load - See note below</li> </ul>
	6070082	<p>Universal LT50 Motor Bracket (LS Style) for 10 mm Square Stud</p> <ul style="list-style-type: none"> <li>- Zinc-plated steel</li> <li>- Maximum motor torque - 25 Nm</li> <li>- Horizontally and vertically adjustable</li> <li>- Maximum system load - 57 Kg. (126 Lbs.)</li> <li>- Replaces SOMFY Cat. No. 6070081</li> </ul>
	6070138	<p>"U" Shape LS Style Motor Bracket for 10 mm Square Stud</p> <ul style="list-style-type: none"> <li>- Maximum motor torque - 25 Nm</li> <li>- Zinc-plated steel</li> <li>- Maximum system load - See note below</li> <li>- Replaces SOMFY Cat. No. 6070137</li> </ul>
	6070182	<p>Heavy Duty Angle Plate</p> <ul style="list-style-type: none"> <li>- For ceiling and wall installation in combination with Cat. No. 6070503</li> <li>- Black oxide finish</li> <li>- Compatible with brackets 6070503, 6080026 and 6080116</li> <li>- Maximum motor torque - 100 Nm</li> <li>- Maximum system load - See note below</li> </ul>
	6070238	<p>LT50 Round Anti-Vibration Motor Bracket</p> <ul style="list-style-type: none"> <li>- Zinc plated steel with a 10 mm molded square stud insert surrounded by rubber</li> <li>- Compatible with matching idler end Cat. #6080206</li> <li>- Can be mounted on 6070526</li> <li>- Maximum motor torque - 20Nm</li> <li>- Can reduce sound levels by 4-5 dB</li> <li>- Maximum system load - See note below</li> </ul>
	6070256	<p>Motor Bracket LT60 FTS</p> <ul style="list-style-type: none"> <li>- Zinc plated steel, gauge 3 (0.24 in.)</li> <li>- Recommended for use with LT FTS 60 (Fabric Tension System)</li> <li>- Maximum motor torque - 100 Nm</li> <li>- Includes universal bracket with spring ring that must be used</li> <li>- Maximum system load - 200 kg. (441 Lbs.)</li> <li>- Spring must be replaced with a locking spring ring 4350027 to obtain full torque and load capability.</li> </ul>

Note: Maximum system load will vary depending on application. SOMFY recommends testing of component in actual application to determine its suitability.